

Range constructor for `std::string_view` 2: Constrain Harder

Document #: R1989R1
Date: 2021-01-17
Project: Programming Language C++
Audience: LWG
Reply-to: Corentin Jabot <corentin.jabot@gmail.com>

Abstract

in Belfast, LWG accepted P1391 partially over concern about the constraints for the range constructor, and as such only the iterator+sentinel constructor was accepted. Please refer to P1391 for the design of the proposed changed. (P1391 being now accepted, I needed a new paper number for the range constructor.)

Revisions

R1

- Fix some typos and other issues in section 2.1
- Add a link to a libstdc+ implementation of the proposal
- Wording tweaks

Issues found during wording reviews

The current idiomatic way to construct a `string_view` is to define a `string_view` operator on user-defined classes, as does `std::string`, `QString` Boost Beast, `fmt` and other. With the changes as proposed in P1391R3, the range constructor may be selected over the conversion function. This is not observable in practice, unless the `string_view` returned by the conversion function is not the same value as what the range constructor would create.

```
struct buffer {  
    buffer() {};  
    char const* begin() const { return data; }  
    char const* end() const { return data + 42; }  
    operator basic_string_view<char, s>() const {  
        return basic_string_view<char, s>(data, data + 2);  
    }  
private:  
    char data[42];  
};
```

To make sure this conversion function keeps getting selected, we had the following constraint

- `std::remove_cvref_t<R>` has no `basic_string_view<charT, traits>` conversion operator.

With that constraint, any type that has a conversion operator will use that conversion operator. If a const type has a non-const conversion function the program remains ill-formed.

Conversion between `string_view` types with different `charT` or different `type_traits` are ill-formed.

If a type otherwise satisfying the constraints has a conversion operator to a different `basic_string_view`, notably `basic_string_view<charT, some-other-traits-type>`, while not itself defining using `type_traits = some-other-traits-type`, a program that was previously ill-formed will call the new range overload.

Implementability

The following overload satisfies the desired set of constraints

```
template <typename T, typename Traits>
concept has_compatible_traits = !requires { typename T::traits_type; }
|| ranges::same_as<typename T::traits_type, Traits>;

template<typename charT, typename traits = std::char_traits<char>>
struct basic_string_view {
    //...
    template <ranges::contiguous_range R>
    requires ranges::sized_range<R>
    && (!std::is_convertible_v<R, const charT*>)
    && std::is_same_v<std::remove_cvref_t<ranges::range_reference_t<R>>, charT>
    && has_compatible_traits<R, traits>
    && (!requires (std::remove_cvref_t<R> & d) {
        d.operator ::std::basic_string_view<charT, traits>());
    })
    basic_string_view(R&&);
}
```

This has been implemented in `libstdc++` such that it passes the set of tests [\[Github\]](#)

Proposed wording

Change in **[string.view] 20.4.2:**

```
template<class charT, class traits = char_traits<charT>>
class basic_string_view {
public:
    [...]
```

```

// construction and assignment
constexpr basic_string_view() noexcept;
constexpr basic_string_view(const basic_string_view&) noexcept = default;
constexpr basic_string_view& operator=(const basic_string_view&) noexcept = default;
constexpr basic_string_view(const charT* str);
constexpr basic_string_view(const charT* str, size_type len);
template <class It, class End>
constexpr basic_string_view(It begin, End end);
template <class R>
constexpr basic_string_view(R&& r);

[...]
};

template<class R>
basic_string_view(R&&)
-> basic_string_view<ranges::range_value_t<R>>;

template<class It, class End>
basic_string_view(It, End) -> basic_string_view<iter_value_t<It>>;

```

Change in **[string.view.cons]** 20.4.2.1:

Add after 7

```

template <class R>
constexpr basic_string_view(R&& r);

```

Constraints:

- R satisfies `ranges::contiguous_range`,
- R satisfies `ranges::sized_range`,
- `is_same_v<ranges::range_value_t<R>, charT>` is true,
- `is_convertible_v<R, const charT*>` is false,
- `r.operator ::std::basic_string_view<charT, traits>()` is not a valid expression, and
- If the qualified-id `R::traits_type` is valid and denotes a type, `is_same_v<remove_reference_t<R>::traits_type, traits>` is true.

Preconditions:

- R models `ranges::contiguous_range`, and
- R models `ranges::sized_range`.

Effects: Initializes `data_` with `ranges::data(r)` and `size_` with `ranges::size(r)`.

Throws: Any exception thrown by `ranges::data(r)` and `ranges::size(r)` throw.

Add to the section [string.view.deduct] the following deduction guides:

```
template<class R>  
basic_string_view(R&&  
-> basic_string_view<ranges::range_value_t<R>>;
```

Constraints: R satisfies ranges::contiguous_range.